



Pretoria West
087 654 6200
sales@genpower.co.za
Silverlakes
087 654 6201
silverlakes@genpower.co.za

PRODUCT SPECIFICATIONS - PERKINS 24KVA STANDBY GENERATOR

ENGINE		ALTERNATOR	
Make	Perkins	Brand	Marelli Motori or Equivalent
Model	404A-22TG	Model	MXB-E180SC4
Type	Turbo Charged	Prime Rating	21.6KVA
No. Of Cylinders	4 - In Line	Standby Rating	24KVA
Starter motor	12V 3.0KW	Power Factor	0,8
Displacement	2216cc	Weight	156KG
Power Output (KW/Min)	27.7kWm@ 1500RPM	Type	Brushless with rotating rectifier
Oil Capacity	10.6L(Sump Maximum)	AVR	M00FA122A
Weight	242KG (Dry)	Pole Nr	4
Governor	Electronical		

ENCLOSURE (OPTIONAL)		CONTROLLER	
Brand	Genpower Electrical	Brand	Deep Sea Electronics
Model	SS	Model	7320MKII
Material	Mild Steel	DC Supply	8-35V Continuous
Thickness	1.6mm	Mains Supply	15-415V (Ph to N)
Paint	Beige Powdercoat	Frequency Range	3-75Hz
Weight (estimate)	223kg	4G Gateway	Optional Extra
Doors	5	Operating Temp	-30°C to +70° C
Lockable	Yes	Output	15V DC for fuel & crank

GENERAL SPECIFICATIONS	
Model	GPB24P-1
Prime Rating	21.6kVA
Standby Rating	24kVA
Voltage	220V Single phase
Frequency	50Hz
Power Factor	0,8
Tank Size	180L
Engine Speed	1500RPM
Length	2000mm
Width	700mm
Height	1000mm
Weight (Approx.)	800KG
Noise Level (Enclosed)	72dB @7m
Fuel Consumption @ 50/75/100%	3.5-8.3L/Hour
Deration of power	-1% per 100M ASL

