



Pretoria West
 087 654 6200
sales@genpower.co.za
 Silverlakes
 087 654 6201
silverlakes@genpower.co.za

PRODUCT SPECIFICATIONS - PERKINS 275KVA STANDBY GENERATOR

ENGINE		ALTERNATOR	
Brand	Perkins	Brand	Marelli Motori or Equivalent
Model	1206A-E70TTAG3	Model	MXB-E250MB4
Type	Turbocharged	Prime Rating	247KVA
No. Of Cylinders	6 - In Line	Standby Rating	275KVA
Starter motor	12V 3.0KW	Power Factor	0,8
Displacement	7000cc	Weight	599KG
Power Output (KW/Min)	248.6kWm@ 1500RPM	Type	Brushless with rotating rectifier
Oil Capacity	16L(Sump Maximum)	AVR	M00FA122A
Weight	877KG (Dry)	Pole Nr	4
Governor	Electronical		

ENCLOSURE (OPTIONAL)		CONTROLLER	
Brand	Genpower Electrical	Brand	Deep Sea Electronics
Model	XL	Model	7320MKII
Material	Mild Steel	DC Supply	8-35V Continuous
Thickness	1.6mm	Mains Supply	15-415V (Ph to N)
Paint	Beige Powdercoat	Frequency Range	3-75Hz
Weight (estimate)	750kg	4G Gateway	Optional Extra
Doors	5	Operating Temp	-30°C to +70° C
Lockable	Yes	Output	15V DC for fuel & crank

GENERAL SPECIFICATIONS	
Model	GPB275P-3
Prime Rating	247kVA
Standby Rating	275kVA
Voltage	380V 3 phase
Frequency	50Hz
Power Factor	0,8
Tank Size	800L
Engine Speed	1500RPM
Length	3500mm
Width	1400mm
Height	1600mm
Weight (Approx.)	2250KG
Noise Level (Enclosed)	72dB @7m
Fuel Consumption @ 50/75/100%	15.4-64.5L/Hour
Deration of power	-1% per 100M ASL

