



Pretoria West  
 087 654 6200  
[sales@genpower.co.za](mailto:sales@genpower.co.za)  
 Silverlakes  
 087 654 6201  
[silverlakes@genpower.co.za](mailto:silverlakes@genpower.co.za)

**PRODUCT SPECIFICATIONS - PERKINS 72KVA STANDBY GENERATOR**

ENGINE		ALTERNATOR	
Brand	Perkins	Brand	Marelli Motori or Equivalent
Model	1104A-44TG1	Model	MXB-E225XB4
Type	Turbocharged	Prime Rating	65KVA
No. Of Cylinders	4 - In Line	Standby Rating	72KVA
Starter motor	12V 3.0KW	Power Factor	0,8
Displacement	4400cc	Weight	296KG
Power Output (KW/Min)	65.6kW@ 1500RPM	Type	Brushless with rotating rectifier
Oil Capacity	7.0L(Sump Maximum)	AVR	M00FA122A
Weight	463KG (Dry)	Pole Nr	4
Governor	Mechanical		

ENCLOSURE (OPTIONAL)		CONTROLLER	
Brand	Genpower Electrical	Brand	Deep Sea Electronics
Model	M	Model	7320MKII
Material	Mild Steel	DC Supply	8-35V Continuous
Thickness	1.6mm	Mains Supply	15-415V (Ph to N)
Paint	Beige Powdercoat	Frequency Range	3-75Hz
Weight (estimate)	000kg	4G Gateway	Optional Extra
Doors	5	Operating Temp	-30°C to +70° C
Lockable	Yes	Output	15V DC for fuel & crank

GENERAL SPECIFICATIONS	
Model	GPB72P-3
Prime Rating	65kVA
Standby Rating	72kVA
Voltage	380V 3 phase
Frequency	50Hz
Power Factor	0,8
Tank Size	470L
Engine Speed	1500RPM
Length	2900mm
Width	1100mm
Height	1200mm
Weight (Approx.)	1100KG
Noise Level (Enclosed)	72dB @7m
Fuel Consumption @ 50/75/100%	4.6-14.8L/Hour
Deration of power	-1% per 100M ASL

