



Pretoria West
 087 654 6200
sales@genpower.co.za
 Silverlakes
 087 654 6201
silverlakes@genpower.co.za

PRODUCT SPECIFICATIONS - PERKINS 900KVA STANDBY GENERATOR

ENGINE		ALTERNATOR	
Brand	Perkins	Brand	Marelli Motori or Equivalent
Model	4006-23TAG3A	Model	MJB400MB4
Type	Turbocharged	Prime Rating	810KVA
No. Of Cylinders	6 - In Line	Standby Rating	900KVA
Starter motor	12V 3.0KW	Power Factor	0,8
Displacement	22921cc	Weight	2300KG
Power Output (KW/Min)	760kWm@ 1500RPM	Type	Brushless with rotating rectifier
Oil Capacity	113.4L(Sump Maximum)	AVR	M40FA640A
Weight	2524kg (Dry)	Pole Nr	4
Governor	Electronical		

ENCLOSURE (OPTIONAL)		CONTROLLER	
Brand	Genpower Electrical	Brand	Deep Sea Electronics
Model	4XL	Model	7320MKII
Material	Mild Steel	DC Supply	8-35V Continuous
Thickness	1.6mm	Mains Supply	15-415V (Ph to N)
Paint	Beige Powdercoat	Frequency Range	3-75Hz
Weight (estimate)	1800kg	4G Gateway	Optional Extra
Doors	7	Operating Temp	-30°C to +70° C
Lockable	Yes	Output	15V DC for fuel & crank

GENERAL SPECIFICATIONS	
Model	GPB900P-3
Prime Rating	810kVA
Standby Rating	900kVA
Voltage	380V 3 phase
Frequency	50Hz
Power Factor	0,8
Tank Size	TBA
Engine Speed	1500RPM
Length	5200mm
Width	1800mm
Height	2200mm
Weight (Approx.)	9000KG
Noise Level (Enclosed)	72dB @7m
Fuel Consumption @ 50/75/100%	90-194L/Hour
Deration of power	-1% per 100M ASL

